



*United States Probation Office
Southern District of
California*

REQUEST FOR QUOTATION (RFQ): D09CASP 2025-0001

DATED: January 31, 2025

NIJ: BA-2000S-SX02 Body Armor or equivalent

The United States Probation Office for the Southern District of California is seeking the above referenced equipment/item, **quantity: up to 20**

ORGANIZATION:

United States Court
U.S. Probation Office Southern
District of California
101 West Broadway, Suite 700 San
Diego, CA 92101-7991

The organization is a Judiciary Branch of the Federal Government and is exempt from state and local taxes. The tax-exempt number is 95-6565020.

CONTACT:

Brian Perkins
Contracting Officer
Budget, Purchasing & Finance Administrator
Voice: (619) 557-7149
FAX: (619) 615-6007
Cell: (619) 894-6023
brian_perkins@casp.uscourts.gov

Closing date: February 28, 2025 (Pacific), 12:00 (noon).

Contract will be awarded on the lowest cost, technically acceptable proposal.

BODY ARMOR

TECHNICAL SPECIFICATIONS

SX02/SX02F - IIIA

CONFIGURATION	Neutral & Structured
ARMOR MATERIAL	Honeywell® Spectra Shield®, Honeywell® Gold Shield®, DuPont™ Kevlar®, SAATI, or equivalent in durability and safety standards
ARMOR PANEL COVERING	Dual Covered, 2-Ply, Laminated 4-way Stretch Polyknit and TPU Lamination System

MUST MEET OR EXCEED TECHNICAL AND PERFORMANCE STANDARDS LISTED BELOW

TECHNICAL SPECIFICATION

MODEL	BA-3A00S-SX02	BA-3A00S-SX02F
THREAT TYPE	Ballistic Level IIIA	Ballistic Level IIIA
TEST STANDARD	NIJ Standard: 0101.06	NIJ Standard: 0101.06

PERFORMANCE

AREAL DENSITY	0.83 lbs/ft² (4.06 kg/m²)	0.85 lbs/ft² 4.30 kg/m² *
THINNESS	0.190 in (4.82 mm)	0.200 in (5.08 mm) *
NEW V50 - .357 SIG FMJ FN 125 GR.	1912 ft/s (583 m/s)	Front Panel: 1891 ft/s (576 m/s) Back Panel: 1912 ft/s (583 m/s) **
CONDITIONED V50 - .357 SIG FMJ FN 125 GR.	1833 ft/s (559 m/s)	Front Panel: 1870 ft/s (570 m/s) Back Panel: 1833 ft/s (559 m/s) **
NEW V50 - .44 MAG JSP 240 GR.	1740 ft/s (530 m/s)	Front Panel: 1670 ft/s (509 m/s) Back Panel: 1740 ft/s (530 m/s) **
CONDITIONED V50 - .44 MAG JSP 240 GR.	1670 ft/s (509 m/s)	Front Panel: 1679 ft/s (512 m/s) Back Panel: 1670 ft/s (509 m/s) **
BACKFACE AVERAGE - .357 SIG	29.20 mm	30.46 mm *
BACKFACE AVERAGE - .44 MAG	37.30 mm	38.21 mm *

***In accordance with NIJ 0101.06 Female Testing the front panel must be tested separately from the back panel.
This is an average of both the front and back panels.

Additional requirements: vendor will conduct on-site custom measurements at 101 W. Broadway San Diego, CA 92101